

## GP-T1880

### 2-Port Indoor FTTH Termination Box

#### Application

- The Fiber Wall Outlet is a compact indoor termination box designed for FTTH last-drop connections in homes, offices, and multi-dwelling units.
- It supports wall mounting and surface mounting with screws or adhesive tape for quick and discreet installation.





#### Features & Benefits

- The GP-T1880 Fiber Wall Outlet 2-Port Inline provides clean, professional termination for 1 incoming and 1 outgoing drop cable.
- It supports 1 SC simplex or LC duplex adapter with inline cable entry for minimal bending radius.
- The outlet accommodates up to 6 fusion splices using integrated heat-shrink splice holders.
- Made from high-impact ABS material with optional UL94-V0 flame-retardant rating for enhanced safety.
- Compact dimensions of 188 × 88 × 22 mm allow installation in tight spaces and behind furniture.
- Operating temperature range of -40°C to +70°C ensures reliable performance in various indoor environments.
- Tool-less snap-lock cover enables fast access for installation and future maintenance.

## Specifications

Part No.	GP-T1880
Dimensions	188 × 88 × 22 mm
Material	ABS (UL94 V0 Optional)
Color	Black (Customizable)
Mounting	Wall Mount
IP Rating	IP20
Cable Entries	1 / 1 In-line
Supported Cable	Ø3 mm Round Drop Cable
Patching Capacity	1 SC Adapter
Splicing Capacity	6 Fibers
Operating Temperature	-40°C to +70°C

## Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Splice Sleeves	Ø1.2 × 45mm	6 PCS

## Ordering Information

Part No.	Description
GP-T1880	Empty box (no adapters, no pigtails)

- ◆ Other configurations are available upon request. Customization supported.

## Packing List

Part No.	PCS / CTN	G.W. / CTN	Carton Size
GP-T1880	100	20KG	53 × 31 × 41 CM

- ◆ Default packaging: one unit per transparent PE bag (cost-effective, most popular).
- ◆ Individual inner box is available as customized packaging. Extra charge applies.