

GP-T404S8

Fiber Optic Floor Terminal Box

Application

- Engineered for FTTH in multi-dwelling units, positioned on each level as a transition between riser and horizontal cables.
- Facilitates storage for excess and terminated fibers while serving as an effective splice point..






Features & Benefits

- Constructed from high-strength engineering alloy plastic for extended durability.
- Removable cover with specialized screw lock for secure access.
- Splice tray flip design maintains a bend radius exceeding 30mm.
- Internal space divided into two sections for loop-through cables and pigtail splicing.
- IP43 rating provides protection against environmental elements.
- Supports two main cables (Ø13 mm) and twenty drop ports (Ø3 mm).

Specifications

Part No.	GP-T404S8
Dimensions	133×103×30 mm
Enclosure Material	ABS or PC/ASB
Main Cable Port	2 × Ø13mm
Drop Cable Port	20 × Ø3mm
Patching Capacity	Not Supported
Splicing Capacity	6/12 Fibers
Splice tray	1 Tray
IP Rating	IP43
Mounting	Wall Mount

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Nylon Cable Tie	3×100mm	10 PCS
	Splice Sleeve	1.2/45mm	12 PCS

Packing List

Part No.	Carton Size	PCS/CTN	G.W.
GP-T404S8	52×45×34 CM	114	23 KGS