

## GP-T861

### 2-Core FTTH Fiber Wall Outlet

#### Application


- The Standard 86 Type Fiber Optic Outlet is a wall-mounted or flush-mounted termination box for end user, indoor use, capable of handling fiber fusion, fiber cables, and pigtails.
- It is compatible with standard electrical wall plates and supports SC adapters for seamless integration.



#### Key Features

- The wall outlet supports dual connectivity with up to two SC simplex adapters for termination and splice connections.
- The ultra-flat profile measures 80 x 80 x 20.5 mm to fit flush against walls or electrical outlets.
- Multi-directional cable entry includes bottom, left, and rear openings for flexible installation options.
- Optimized internal routing maintains a minimum 30 mm bend radius to protect fiber integrity.
- SC adapters can be inverted in holders to prevent accidental disconnection when cables are pulled.
- The IP20 rating provides basic dust protection suitable for indoor environments.
- Tool-less access features an easy-open design for quick maintenance and installation.



#### Dimension Drawing



## Specifications

| Part No.              | GP-T861                               |
|-----------------------|---------------------------------------|
| Dimensions            | 86 × 86 × 21.5 mm                     |
| Material              | ABS (UL94 V0 Optional)                |
| Color                 | White (Customizable)                  |
| Mounting              | Wall Mount                            |
| IP Rating             | IP20                                  |
| Cable Entries         | 2                                     |
| Supported Cable       | Ø3 mm Round or 3×2 mm Flat Drop Cable |
| Storage of Fibers     | G.657 Fiber                           |
| Adapter Ports         | 2                                     |
| Adapter Type          | SC or LC Duplex Adapter               |
| Splicing Capacity     | 2/4 Fibers                            |
| Splicing Method       | Fusion Splice                         |
| Compatible Fiber      | G.657A1/A2/B3                         |
| Operating Temperature | -40°C to +70°C                        |

## Accessories

| Picture   | Name              | Size         | Quantity |
|---|-------------------|--------------|----------|
|  | Wall-mounting Kit | /            | 2 Pairs  |
|  | Splice Sleeve     | Ø1.2 × 45 mm | 2 PCS    |

## Ordering Information

| Part No.      | Description   |
|---------------|---|
| GP-T861       | Empty box (no adapters, no pigtails)                                      |
| GP-T861-2A    | Fully loaded with 2 × SC/APC adapters                                     |
| GP-T861-2A-2P | Fully loaded with 2 × SC/APC adapters + 2 × SC/APC pigtails (900 µm, 1 m) |

- ◆ Other configurations are available upon request. Customization supported.

## Packing List

| Part No. | PCS / CTN | G.W. / CTN | Carton Size     |
|----------|-----------|------------|-----------------|
| GP-T861  | 400       | 22 KG      | 51 × 46 × 38 CM |

- ◆ Default packaging: one unit per transparent PE bag (cost-effective, most popular).
- ◆ Individual inner box is available as customized packaging. Extra charge applies.