

GP-T863

2-Core FTTH Flip-Cover Wall Outlet

Application

- The GP-T863 is designed for indoor FTTH network splicing and fiber management, providing a compact, secure enclosure for fusion splicing, termination, and organized storage of fiber optic cables.
- IP20 Rated, for wall-mounted or flush-mounted installations in residential buildings, office complexes, and telecom distribution points requiring reliable fiber protection and easy maintenance.



Key Features

- Hinged Flip-Cover Design - Tool-free access with a durable hinge mechanism for quick splicing and maintenance.
- Fusion Splice Capacity - Supports up to 2 fiber splices with integrated splice tray organization.
- Dual SC Adapter Integration - Pre-installed 2 SC adapters for seamless connectivity in FTTH networks.
- Engineered Fiber Routing - Guided channels ensure a protected bend radius (>30mm) to safeguard fiber integrity.
- Compact Wall-Mount - Slim profile (86x86x26mm / 3.39x3.39x1.02in) for discreet installation in tight spaces.
- Durable & Aesthetic Housing - High-impact plastic with RAL9001 white finish, resistant to wear and blending into indoor environments.

Specifications

Part No.	GP-T863
Dimensions	86 × 86 × 26 mm
Material	ABS (UL94 V0 Optional)
Color	White (Customizable)
Mounting	Wall Mount
IP Rating	IP20
Cable Entries	2
Supported Cable	Ø3 mm Round or 3×2 mm Flat Drop Cable
Storage of Fibers	G.657 Fiber
Adapter Ports	2
Adapter Type	SC or LC Duplex Adapter
Splicing Capacity	1/2 Fibers
Splicing Method	Fusion Splice
Compatible Fiber	G.657A1/A2/B3
Operating Temperature	-40°C to +70°C

Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Splice Sleeve	Ø1.2 × 45 mm	1 or 2 PCS

Ordering Information

Part No.	Description
GP-T863	Empty box (no adapters, no pigtails)
GP-T863-2A	Fully loaded with 2 × SC/APC adapters
GP-T863-2A-2P	Fully loaded with 2 × SC/APC adapters + 2 × SC/APC pigtails (900 µm, 1 m)

- ◆ Other configurations are available upon request. Customization supported.

Packing List

Part No.	PCS / CTN	G.W. / CTN	Carton Size
GP-T863	200	6 KG	36 × 45 × 30 CM

- ◆ Default packaging: one unit per transparent PE bag (cost-effective, most popular).
- ◆ Individual inner box is available as customized packaging. Extra charge applies.