

## GP-T868

### 1/2-Core FTTH Wall Outlet

#### Application

- The 1/2-Core FTTH Wall Outlet is the most compact FTTX network distribution node equipment, offering quick and reliable connections, excellent protection, and efficient management for the FTTX network.
- It is rated IP20 and is specifically designed for indoor wall-mount applications\.



#### Features & Benefits

- The wall outlet delivers the most compact structure design available, making it ideal for space-constrained indoor environments.
- It includes a dedicated splice tray that supports up to 2 fusion splices (2/4 fibers).
- The product is constructed from high-quality ABS material for durability and long-term performance.
- It provides an IP20 rating to ensure reliable indoor protection against solid objects.
- Wall-mount installation is simple and secure with the included mounting kit.
- It supports one SC simplex or LC Duplex adapter plus three blind ports for flexible cable entry and exit.
- Ultra-compact dimensions of 115 × 86 × 23 mm allow discreet and professional installation in homes or offices.

## Specifications

Part No.	GP-T868
Dimensions	115 × 86 × 23 mm
Material	ABS (UL94 V0 Optional)
Color	White (Customizable)
Mounting	Wall Mount
IP Rating	IP20
Cable Entries	3
Supported Cable	Ø3 mm Round or 3×2 mm Flat Drop Cable
Storage of Fibers	G.657 Fiber
Adapter Ports	1
Adapter Type	SC or LC Duplex Adapter
Splicing Capacity	2/4 Fibers
Splicing Method	Fusion Splice
Compatible Fiber	G.657A1/A2/B3
Operating Temperature	-40°C to +70°C

## Accessories

Picture	Name	Size	Quantity
	Wall-mounting Kit	/	2 Pairs
	Cable Tie	3 × 100 mm	3 PCS
	Splice Sleeve	Ø1.2 × 45 mm	2 PCS

## Ordering Information

Part No.	Description
GP-T868	Empty box (no adapters, no pigtails)
GP-T868-1A	Fully loaded with 1 × SC/APC adapters
GP-T868-1A-1P	Fully loaded with 1 × SC/APC adapters + 1 × SC/APC pigtails (900 µm, 1 m)

- ◆ Other configurations are available upon request. Customization supported.

## Packing List

Part No.	PCS/CTN	G.W. / CTN	Carton Size
GP-T868	200	16 KGS	59 × 45 × 25 CM

- ◆ Default packaging: one unit per transparent PE bag (cost-effective, most popular).
- ◆ Individual inner box is available as customized packaging. Extra charge applies.\